



ELKAY

Outdoor ezH2O bi-nivel

LK4420BF1UEVG · pedestal para exterior

ESPECIFICACIONES

Montaje	piso · pedestal bi-nivel
Uso	intemperie
Acabado	Evergreen · también gris, azul y negro
Construcción	acero inoxidable 300 con pintura en polvo
Dimensiones	356 × 787 × 1.626 mm
Certificaciones	ADA · NSF/ANSI 61 y 372 · ASME

INSTRUCTIVO DE USO

- 01 El bebedero, cuando lo tiene, se acciona con el pulsador frontal o lateral.
- 02 El contador Green Ticker suma cada botella plástica evitada.
- 03 La estación de llenado se acciona con pulsador mecánico, apto para intemperie.

CUIDADO Y MANTENIMIENTO

- 01 Limpiar acero y plásticos con paño suave y detergente neutro; no usar abrasivos ni cloro concentrado.
- 02 En versiones filtradas, cambiar el WaterSentry Plus cada 12 meses o 3.000 galones; el indicador avisa.
- 03 Instalación y regulación de caudal a cargo del servicio técnico de Equipamiento.

Instalación y servicio técnico: Equipamiento S.R.L. Los equipos se entregan en 220 V, listos para Bolivia. La instalación, el recambio de filtros y el mantenimiento semestral los realiza nuestro equipo técnico con repuestos originales en stock.

PRODUCT SPECIFICATIONS



Outdoor ezH2O® Upper Bottle Filling Station Bi-Level Pedestal Non-Filtered Non-Refrigerated. Features shall include Heavy Duty Vandal Resistant, Laminar Flow, 300 Series Stainless. Furnished with Vandal Resistant bubbler. Mechanical Button activation. Product shall be Floor Mount/Freestanding, for Outdoor applications, serving 2 station(s).

Special Features:	Heavy Duty Vandal Resistant, Laminar Flow, 300 Series Stainless
Finish:	Black (BK), Blue (BLU), Evergreen (EVG), Gray (GRY)
Power:	No Electrical Required
Bubbler Style:	Vandal Resistant
Activation by:	Mechanical Button
Mounting Type:	Floor Mount/Freestanding
Chilling Capacity:	Non-refrigerated
Dimensions (L x W x H):	14" x 31" x 64"
Approx. Shipping Weight:	147 lbs.
Installation Location**:	Outdoor
No. of Stations Served:	2

**When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

Special Note: To meet the full requirements for ADA please choose LK4430BF1L for adult installations and LK4430BF1M for child ADA. Bottle Filler Stations 1 (Upper), Bubbler Stations 1 (Low), Choose from 4 color options

- Mechanically-Activated unit continues to supply water in event of service disruptions.
- Laminar flow provides clean fill with minimal splash.



Included with Product: Outdoor Bottle Filler
Ships in one box.

A Century of Tradition and Quality. For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.

PRODUCT COMPLIANCE

ADA & ICC A117.1

ASME A112.19.3/CSA B45.4

GreenSpec®

NSF/ANSI 61 (Q≤1) & 372 (lead free)

NSF REG4



Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

[Installation Instructions \(PDF\) - 1000003685](#)

Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.

[Warranty \(PDF\)](#)

PART: _____ QTY: _____

PROJECT: _____

CONTACT: _____

DATE: _____

NOTES: _____

APPROVAL: _____

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.